

POWER TOOLS & ABRASIVES

MAKITA POWER TOOLS เครื่องมือไฟฟ้า “มาคิต้า”



มาคิต้า

HS009G Cordless Circular Saw 40V max

40Vmax XGT BL AWS Cordless 235 mm (9-1/4")
Magnesium Circular Saw, Electric Brake, Soft Start,
Twin LED Light



Blade Diameter	235 mm (9-1/4")
Max Cutting Capacity	0°: 85 mm (3-3/8") 45°: 61 mm (2-3/8") 60°: 44 mm (1-3/4")
No Load Speed (RPM)	4,000
Dimensions (L x W x H)	413 x 196 x 316 mm (16-1/4 x 7-3/4 x 12-1/2")
Net weight	5.1 - 5.7 kg (11.2 - 12.6 lbs.)

HS003G Cordless Circular Saw 40V max

40Vmax XGT BL AWS ADT Cordless 190/185 mm (7-1/2" / 7-1/4")
Magnesium Circular Saw, Electric Brake,
Soft Start, Twin LED Light



Blade Diameter	190 / 185 mm (7-1/2" / 7-1/4")
Max Cutting Capacity	0°: 68.5, 66 mm (2-11/16, 2-5/8") 45°: 47.5, 45.5 mm (1-7/8, 1-13/16") 56°: 35.5 / 34 mm (1-3/8 / 1-5/16")
No Load Speed (RPM)	6,000
Dimensions (L x W x H)	w/ BL4020 / BL4025: 316 x 200 x 290 mm (12-1/2 x 7-7/8 x 11-3/8") w/ BL4040: 331 x 200 x 290 mm (13 x 7-7/8 x 11-3/8")
Net weight	4.1 - 4.4 kg (9.0 - 9.7 lbs.)

HS004G Cordless Circular Saw 40V max

40Vmax XGT BL AWS ADT Cordless 190/185 mm (7-1/2" / 7-1/4")
Magnesium Circular Saw, Electric Brake, Soft Start, Twin LED Light



Blade Diameter	190 / 185 mm (7-1/2" / 7-1/4")
Max Cutting Capacity	0°: 62.5, 60 mm (2-7/16, 2-3/8") 45°: 44.5, 43 mm (1-3/4, 1-11/16") 48°: 42, 41 / 42, 41 mm (1-5/8, 1-5/8 / 1-5/8, 1-5/8")
No Load Speed (RPM)	6,000
Dimensions (L x W x H)	w/ BL4020 / BL4025: 322 x 210 x 290 mm (12-5/8 x 8-1/4 x 11-3/8") w/ BL4040: 337 x 210 x 290 mm (13-1/4 x 8-1/4 x 11-3/8")
Net weight	4.4 - 4.7 kg (9.7 - 10.4 lbs.)

SP001G Cordless Plunge Cut Saw 40V max

40Vmax XGT BL Cordless 165 mm (6-1/2")
Plunge Cut Saw



Wheel Diameter	165 mm (6-1/2")
Blade Diameter	165 mm (6-1/2")
Hole Diameter	20 mm (13/16")
Bevel Capacity	-1 - 48°
Max Cutting Capacity	0°: 56 mm (2-3/16") 45°: 40 mm (1-9/16") 48°: 38 mm (1-1/2")
No Load Speed (RPM)	2,500 - 4,900
Dimensions (L x W x H)	347 x 221 x 271 mm (13-5/8 x 8-3/4 x 10-5/8")
Net weight	4.4 - 5.0 kg (9.7 - 11.0 lbs.)

JR001G Cordless Recipro Saw 40V max

40Vmax XGT BL Brushless Cordless Recipro Saw



Length of Stroke	32 mm (1-1/4")
Strokes Per Minute (SPM)	High / Low: 0 - 3,000 / 0 - 2,300
Capacity	Pipe / Wood: 130 / 255 mm (5-1/8" / 10")
Dimensions (L x W x H)	w/ BL4020 / BL4025 : 457 x 88 x 233 mm (18 x 3-1/2 x 9-1/8") w/ BL4040: : 472 x 88 x 239 mm (18-5/8 x 3-1/2 x 9-3/8")
Net weight	4.2 - 4.5 kg (9.3 - 9.9 lbs.)

JR002G Cordless Recipro Saw 40V max

40Vmax XGT BL AVT Cordless Recipro Saw



Length of Stroke	32 mm (1-1/4")
Strokes Per Minute (SPM)	0 - 3,000
Capacity	Pipe / Wood: 130 / 255 mm (5-1/8" / 10")
Dimensions (L x W x H)	w/ BL4020 / BL4025 : 436 x 97 x 250 mm (17-1/8 x 3-13/16 x 9-7/8") w/ BL4040: : 446 x 97 x 250 mm (17-5/8 x 3-13/16 x 9-7/8")
Net weight	4.6 - 5.2 kg (10.1 - 11.5 lbs.)

FN001G Cordless Brad Nailer 40V max

40Vmax XGT BL Cordless 18 Ga 40 mm (1-5/8") Brad Nailer



Capacity	Length: 15, 20, 25, 30, 35, 40 mm (5/8, 3/4, 1, 1-3/16, 1-3/8, 1-5/8") Gauge: 18 Ga
Magazine Capacity	100
Shot qty on a single full battery charge	w/ BL4025: 5,000 w
Dimensions (L x W x H)	/ BL4020 / BL4025 : 265 x 86 x 243 mm (10-3/8 x 3-3/8 x 9-9/16") w/ BL4050F: : 291 x 86 x 263 mm (11-1/2 x 3-3/8 x 10-3/8")
Net weight	2.6 - 3.2 kg (5.7 - 7.1 lbs.)

MP001G Cordless Inflator 40V max

Cordless Inflator



Air Discharge Amount	200 kPa: 24 L/min 700 kPa: 12 L/min 1,110 kPa (161 PSI) [11.1 bar]
Max Air Pressure	65 cm (25-1/2")
Hose Length	71 dB(A)
Sound Pressure Level	3.8 m/s ²
Vibration Level	w/ BL4020 / BL4025: 320 x 108 x 231 mm (12-5/8 x 4-1/4 x 9-1/8") w/ BL4040: 329 x 108 x 231 mm (13 x 4-1/4 x 9-1/8") w/ BL4050F: 351 x 108 x 231 mm (13-3/4 x 4-1/4 x 9-1/8")
Dimensions (L x W x H)	2.9 - 3.5 kg (6.4 - 7.7 lbs.)
Net Weight	

PDC1200 Portable Power Pack 40V max

36V-40Vmax LXT XGT Li-Ion Portable Power Pack



Capacity	33.5 Ah
Energy Capacity	1,206 Wh
Number of Cells	100
Charging Time (hours)	6
Power Supply Cord	Battery Side: 1.1 m (3.6 ft) Adapter Side: 0.6 m (2.0 ft)
Dimensions (L x W x H)	w/o Harness: 369 x 261 x 139 mm (14-1/2 x 10-1/4 x 5-1/2") w/ Harness: 428 x 261 x 164 mm (16-7/8 x 10-1/4 x 6-1/2")
Net weight	w/o Harness: 8.8 kg (19.4 lbs.)

ML002G Cordless LED Worklight 40V max

40Vmax XGT Li-Ion 21 LED Worklight, 710 Lumens



Run Time (hrs)	Up to: 51
Main light (on bar side)	Luminous flux (Full brightness): 710 lm Illuminance (Full brightness): 340 lx Luminous flux (Half brightness): 340 lm Illuminance (Half brightness): 310 lx
Sub light (on top side)	Luminous flux: 130 lm Illuminance: 1,900 lx
Dimensions (L x W x H)	w/ BL4025 : 376 x 86 x 126 mm (14-3/4 x 3-3/8 x 5") w/ BL4040 : 382 x 86 x 141 mm (15 x 3-3/8 x 5-9/16")
Net weight	1.2 - 1.5 kg (2.7 - 3.3 lbs.)

CW001G Cordless Cooler & Warmer Box 40V max

Cordless Cooler & Warmer Box



Run Time (hrs)	w/ BL4050 X2, -18 / 5 / 60°C: 10 / 28 / 8.5 hrs 20 L (5.3 gal)
Capacity	
Cooling Capacity	-18 / -15 / -10 / -5 / 0 / 5 / 10°C (0 / 5 / 15 / 25 / 30 / 40 / 50°F)
Warming Capacity	30 / 35 / 40 / 45 / 50 / 55 / 60°C (85 / 95 / 105 / 115 / 120 / 130 / 140°F)
Dimensions (L x W x H)	663x341x372 mm (26-1/8x13-3/8x14-5/8")
Net weight (kg)	13.8 - 16.1 kg (30.4 - 35.5 lbs.)

CF002G Cordless Fan 40V max

40Vmax XGT Li-Ion Cordless 330 mm (13") Fan (CF002G)
18V / 14.4V LXT Li-Ion Cordless 330 mm (13") Fan (DCF301)



Continuous Use (min.) w/o oscillation	w/ BL4040 Low / Mid / High : CF002G: 860 / 480 / 260 w/ BL1860B Low / Mid / High : DCF301: 400 / 190 / 120
Max Air Velocity	High / Mid / Low: 240 / 170 / 110 m/min
Air Flow	High / Mid / Low: 21 / 15 / 11 L/min
Fan Diameter	330 mm (13")
Dimensions (L x W x H)	240 x 434 x 560 mm
Net weight	CF002G: 4.0-5.3 kg (8.9-11.7 lbs.) DCF301: 4.0 - 4.7 kg (8.9 - 10.4 lbs.)